
VEXXIS[®] Antennas GNSS-802

CUTTING EDGE ANTENNA TECHNOLOGY WITH SUPERIOR TRACKING PERFORMANCE



INNOVATIVE DESIGN WITH MULTIPLE PATENTS

The VEXXIS GNSS-800 series antennas feature a patented multi-point feeding network and radiation pattern optimization technology. In addition to having enhanced performance in multipath environments, the GNSS-802 antenna is able to maintain a low profile while achieving both high peak zenith gain and low gain roll-off from zenith to horizon, without sacrificing tracking performance. This new technology significantly enhances the low elevation angle tracking capabilities, extending operation to the entire GNSS constellation. Furthermore, the antenna is able to achieve greater phase center stability through our innovative element design. This directly translates into improved carrier phase measurement and a better RTK solution.

TRACKING IN CHALLENGING ENVIRONMENTS

The ability to track low elevation satellites, while maintaining a high gain for higher elevation satellites, makes the GNSS-802 an excellent choice for any applications where the sky is partially visible, such as operating close to tree lines, under foliage or in urban canyons. The antenna is able to track any visible satellites from horizon to zenith, providing the maximum number of observations for an enhanced positioning solution.

NOVATEL'S TOUGHEST PRECISION ANTENNA

GNSS-800 antennas are the toughest high precision antennas NovAtel has designed to date, ensuring their survivability even in the harshest operating environments. The antennas feature ultra-durable watertight enclosures, and have been proven to sustain intense vibration, earning the MIL-STD-810G rating.

FEATURES

- + Supports dual-frequency GPS and GLONASS signals
 - + Multi-point antenna feed provides stable phase center and enhanced multipath rejection
 - + Radiation pattern optimization technology yields exceptional low elevation satellite tracking
 - + Provides exceptional tracking performance previously unachievable in a small form factor
 - + Hermetically sealed enclosure to endure the toughest environments
-

If you require more information about our antennas, visit www.novatel.com/antennas



Sea and Land Technologies Pte Ltd
Global Technologies | Seamless Solution

Main Office & Asia Pacific Service Centre

7 Tuas Basin Link Singapore 638761

+65 6716 0777 +65 6563 0366

GNSS-802

PERFORMANCE

Signal Received	
GPS	L1, L2
GLONASS	L1, L2
Galileo	E1
BeiDou	B1
Pass Band (typical)	
Upper passband	1588.0 ± 23.0 MHz
Lower passband	1234.0 ± 17.0 MHz
Out-of-Band Rejection	
Band edges ± 50 MHz	40 dB minimum
Band edges ± 100 MHz	60 dB minimum
LNA Gain	29 dB (typical)
Gain at Zenith (90°) ¹	
L1/G1	+5.0 dBic minimum
L2/G2	+5.0 dBic minimum
Gain Roll-Off (from Zenith to Horizon)	
L1/E1/B1	10 dB
L2/G1/G2	12 dB
Phase Center Stability	<2.0 mm
Noise Figure	<2.0 dB (typical)
VSWR	≤2.0 : 1
L1-L2 Differential Propagation Delay	5 ns (maximum)
Group Delay Ripple	<15 ns
Nominal Impedance	50 Ω

PHYSICAL AND ELECTRICAL

Dimensions	176 mm D × 55 mm H
Weight	507 g
Connector	TNC female Optional N-Type
Mounting	5/8" thread mount
Power	
Input voltage	+3.8 to +18.0 VDC
Current	60 mA (maximum)

ENVIRONMENTAL

Temperature	
Operating	-40°C to +85°C
Storage	-55°C to +85°C
Humidity	95% non-condensing
Salt Fog	MIL-STD-810G (CH1), 509.6, Procedure I
Dust/Water Resistance	IP69K
Vibration (operating)	
Random	MIL-STD-810G (CH1), 514.7 (7.7 g) Annex E Procedure I, Category 24
Shock	MIL-STD-810G (CH1), 516.7 (40 g), Procedure I
Bump	IEC 60068-2-27 Ea (25 g)

REGULATORY COMPLIANCE

Compliance	FCC, CE
RoHS	EU Directive 2011/65/EU

For the most recent details of this product:
www.novatel.com/products/gnss-antennas/vexxis-series-antennas/gnss-800-series-antennas/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)
or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Version 4 - Specifications subject to change without notice.

©2019 NovAtel Inc. All rights reserved.

NovAtel and VEXXIS are registered trademarks of NovAtel Inc.

Printed in Canada.

D21524 May 2019



¹ G1 zenith gain is 4dBic (typical).